

S6 Plus Android Mobile Computer

S6 Plus has Android OS 7.0 with 4G high speed network communication. Inside the compact handheld device, sealing level of IP65 water/dust proof, 1.5m/4.5ft drop survival, ergonomic design, over-molding structure, quick- charging technology, and 4.7 inch tough Gorilla Glass 3 screen are all equipped to ensure performance. Latest 1.3GHz quad-core processor 2GB RAM/16GB ROM and up to 32GB expansion are all designed to boost up experience level.



FEATURES

➤ **Extremely Stable Performance**

Android 7.0 OS with memory of 2GB RAM/16GB ROM can provide the highly standard experience

➤ **High Speed Data Communication**

Double insurance of 4G high Speed network and dual-frequency WIFI network can ensure the real-time data communication in different using environment;

➤ **Rugged Ergonomic and Over-molding Design**

Over-molding and ergonomic hardware design can satisfy most of the tough environment from different fields;

➤ **Extremely Stable Hardware Display**

4.7 inch Gorilla Glass 3 9H screen can ensure the performance under different tough environment;

➤ **Highly Customized Structure**

'All-in-One' hardware design conception can expand the hardware modules integration based on different project requirements, especially like UHF+HF, UHF+LF; HF+LF;

➤ **Quick-Charging**

Quick-charging technology can provide the most efficient experience;

➤ **Perfect Service**

Professional and skillful service involving the whole life cycle can guarantee the stability.

SPECIFICATIONS		
PHYSICAL CHARACTERISTICS		
Dimension	162mm(H)x78mm(W)x22mm(D)±2 mm	
Weight	Net Weight :<450g (including battery&wrist strap)	
Display	Gorilla Glass 3 9H 4.7 in. TFT-LCD(720x1280)touch screen with backlight	
Backlight	LED backlight	
Keypads	3 TP keys, 5 function keys, 4 side buttons	
Expansions	2 PSAM, 1 SIM, 1 TF	
Battery	Rechargeable li-ion polymer, 3.7V, 4300mAh	
PERFORMANCE CHARACTERISTICS		
CPU	Quad A53 1.3GHz quad-core	
Operating System	Android 7.0	
Storage	2GB RAM, 16GB ROM, MicroSD(max 32GB expansion)	
USER ENVIRONMENT		
Operating Temp.	-20°C to 50°C	
Storage Temp.	-20°C to 70°C	
Humidity	5%RH to 95%RH(non-condensing)	
Drop Specifications	5ft./1.5 m drop to concrete across the operating temperature range	
Sealing	IP65, IEC compliance	
ESD	±15kv air discharge, ±8kv direct discharge	
DEVELOPMENT ENVIRONMENT		
SDK	HHW Software Development Kit	
Language	Java	
Environment	Android Studio or Eclipse	
DATA COMMUNICATION		
WWAN	TDD-LTE Band 38, 39, 40, 41 FDD-LTE Band 1, 2, 3, 4, 7, 17, 20; WCDMA(850/1900/2100MHz); GSM/GPRS/Edge (850/900/1800/1900MHz);	
WLAN	2.4GHz/5.8GHz Dual Frequency, IEEE 802.11 a/b/g/n	
WPAN	Bluetooth Class v2.1+EDR, Bluetooth v3.0+HS, Bluetooth v4.0	
GPS	GPS(embedded A-GPS), accuracy of 5 m	
DATA CAPTUEER		
BARCODE READER(OPTIONAL)		
1D barcode	Symbologies	All major 1D barcodes
2D barcode	2D CMOS Imager	New Land Scan Engine
	Symbologies	PDF417, MicroPDF417, Composite, RSS, TLC-39, Datamatrix, QR code, Micro QR code, Aztec, MaxiCode, Postal Codes, US PostNet, US Planet, UK Postal, Australian Postal, Japan Postal, Dutch Postal. etc.
COLOR CAMERA		

Resolution	8.0 megapixel	
Lens	Auto-focus with LED flash	
RFID READER(OPTIONAL)		
RFID LF	Frequency	125KHz/134.2KHz(FDX-B/HDX)
	Protocol	ISO 11784&11785
	R/W Range	2cm to 10 cm
RFID HF	Frequency	13.56MHz
	Protocol	ISO 14443A&15693
	R/W Range	2cm to 8cm
RFID UHF	Frequency	865~868MHz or 920~925MHz
	Protocol	EPC C1 GEN2/ISO 18000-6C
	Antenna Gain	Circular antenna(2dBi)
	R/W Range	2 m to 4 m(tags and environment dependent)
Active 2.45GHz	Read range more than 200 m	
433MHz	Read range more than 200 m	
PSAM SECURITY(OPTIONAL)		
Protocol	ISO 7816	
Baud rate	9600, 19200, 38400,43000, 56000, 57600, 115200	
Slot	2 slots(maximum)	
ACCESSORIES		
Standard	1xPower Supply; 1xLithium Polymer Battery; 1xDC charging cable; 1xUSB data cable	
Optional	Carrying case; Cradle	