

SCANMAX

Luxurious swing barrier gate

SM-B09BD and SM-B09BS

Technical parameters			
Power voltage	AC220±10%,50Hz	Open angle	90°
Drive voltage	AC12V+AC18V	Pass speed	≦ 30 person/minutes
(Operation condition)	-15℃ ~ +60℃	Structure	304 Stainless Steel
Relative humidity	None-condensation ≦90%	Open direction	Unidirectional or bidirectional
Input signal	Open signal or 12v pulse>100ms	Install place	Outdoor and indoor
Working Current	≦2000mA	IP Degree	IP43
Length of the bar	350 mm	Width of passage	700mm
Service life	≥3 million times	Communication port	RS485,RS232

Features:

- Barriers made from stainless steel, acrylic glass, etc; Mechanical Anti-Pinch structure enable motor to stop working automatically in given time if there is something on the way during reset, and reset again after default time delay
- Automatic counting indicating passenger's number.
- Human base model indication function, real time displaying, improve the passing rate and convenient maintain

SCANMAX

- Anti pinch function, barriers auto open when power shut, insure user safety.
- Break-in ,tail ,over-pass and reverse alert function in order to keep orderliness and effective manage
- Super combination capacity, adjustable model on site
- Barriers move speed auto adjust with card reader, problem self-recovery, error calls function which could convenient users and operators
- Standard input/output port, meanwhile leaving a port space for installing RS485 communication, connect and manage the integrated systems through the remote PC.
- Turned up-coverage is water-proof and easy maintain .
- Open direction adjustable even though power off

Types & Images

Name: Luxurious swing barrier gate

Type: SM-B09BD(Single core)

SM-B09BS(Double core)

SCANMAX



Dimension: 1200*220*980m

Net weight : 50KG

Gross weight:75KG

Packing size: 1290*360*1180mm